

PAB FIRE 05

GLASS FIBRE REINFORCED
THERMOPLASTIC



New, modern design and excellent protection properties. Optimal relationship between protection and comfort with a broad spectrum of optional upgrades. Structural firefighting has never been safer.

PERFORMANCE

- Extreme temperature resistance (up to 1,000°C in a 10 second flash over flames)
- Long-term temperature resistance (radiant heat test 14 kW/m²)
- High resistance to mechanical impacts
- Low-temperature classification -30°C

SAFETY

- Electrical insulation capacity E2 and E3
- Full head protection (including neck and face)
- Interior shock absorber
- Reflective elements for better visibility in low-light conditions
- Neck protector (available in aluminised fibre, Nomex or wool for Holland style)
- 3 point chinstrap (tested to prevent skin irritation, fire retardant aramid tape)
- Chemical resistance (according to EN 443)
- Type B3b

COMFORT

- Lightweight
 - Integrated adjustment system
 - One shell size for head sizes from 52 to 64 cm
- Wide range of accessories and high level of personalisation

WEIGHT

- 1445 g ± 30 g (basic configuration without accessories)
- 1515 g ± 30 g (basic configuration with aluminised neck protector)

HIGH TECH MATERIALS

- Flame retardant and high temperature resistant glass-fiber reinforced thermoplastic
- Anti-scratch and anti-fog coated integrated visor (EN 14458)
- Anti-scratch and anti-fog coated integrated goggle (EN 14458)

MADE IN EUROPE



CERTIFICATES
EN 443:2008 | EN 14458:2018 | MED

ACCESSORIES



COLOR SCALE



PAB Akrapović

Most 26, HR-52420 Buzet, Croatia
P +385 52 662 662 | F +385 52 662 254
info@pab.hr | www.pab.hr